

02/10/00  
jc685 U.S. PTO

S&H Form: PTO/SB/05 (12/97)

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 1046.1209/JDH

First Named Inventor or Application Identifier:

Kazuichi OOE

Express Mail Label No.

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: **Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231**

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract ..... [ Total Pages: 39 ]
3. ☒ Drawing(s) (35 USC 113) ..... [ Total Sheets: 15 ]
4. ☒ Oath or Declaration ..... [ Total Pages: 3 ]
  - a. ☒ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
    - i. ☐ **DELETION OF INVENTOR(S)**  
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - a. ☐ Computer Readable Copy
  - b. ☐ Paper Copy (identical to computer copy)
  - c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [ ] Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449 [X] Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) [ ] Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

17. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information:

[ ] Continuation [ ] Divisional [ ] Continuation-in-part (CIP) of prior application No: 1

## 18. CORRESPONDENCE ADDRESS

STAAS & HALSEY, LLP  
Attn: James Halsey, Jr.  
700 Eleventh Street, N.W., Suite 500  
Washington, DC 20001

Telephone: (202) 434-1500  
Facsimile: (202) 434-1501

## COMMUNICATIONS METHOD AND COMMUNICATIONS DEVICE

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to a data communications  
5 method and a data communications device for setting optimum  
communication conditions between the communications devices  
for performing data communications with each other.

#### 2. Description of the Related Art

A communication speed between communications devices  
10 connected to a network depends upon, in addition to a  
communication performance in terms of hardware in the network,  
a clock cycle of a CPU incorporated into the communications  
device, a version of an OS, specifications of a bus connected  
to the CPU, an accessing speed to a memory from the CPU, and  
15 an execution efficiency of a communications driver for actually  
transmitting and receiving the data by accessing the network.  
Further, the execution efficiency of the communications driver  
changes depending on an OS internal function different per  
version of the OS. The reason is that there might be a case  
20 in which the OS internal function for providing the function  
to a program from the OS changes per version of the OS.

According to the prior art, a performance check is carried  
out when developing a communications driver, and parameters for  
exerting an influence upon the execution efficiency are  
25 adjusted and set, whereby the execution efficiency of the  
communications driver is optimized (which is called "tuning").

The parameters set when developed do not necessarily

continue to be optimum values due to an OS patch (which may be a partial modification of a so-called load module, i.e., an execution module consisting of a binary file), a change in the CPU, a memory extension, etc..

5 Further, in such an environment that computer systems (nodes) different from each other are connected to the same network, it is required that the parameters of the communications driver be manually set per node. It is, however, difficult to actually do the manual setting.

#### SUMMARY OF THE INVENTION

10 It is a primary object of the present invention, which was devised to obviate the problems inherent in the prior art, to provide a function of automatically tuning a communication performance between communications devices connected to a network.

15 It is another object of the present invention to provide a function of periodically confirming and tuning the communication performance.

20 To accomplish the above objects, according to one aspect of the present invention, a communications method of performing communications by switching over a plurality of communication modes comprises followings. The first is a step of measuring a communication performance based on each of the communication modes under a plurality of communication conditions. The second is a step of obtaining, per communication condition, a

condition-based optimum communication mode in which the communication performance in the specific communication mode exceeds a communication performance in other communication mode. The third is a step of selecting the condition-based optimum communication mode in accordance with the communication condition when in communications, and thus performing the communications.

According to another aspect of the present invention, a communications method in the plurality of communications devices each having a storage unit and capable of changing a maximum data size as a basis for a data transfer comprises followings. The storage unit of the communications device is operated with a different operation quantity. Then a completion time of the operation is measured. Then a change in the completion time with respect to a change in the operation quantity is obtained. Finally the maximum data size is determined within a range of the operation quantity in which the change in the completion time is within a predetermined value, thus performing the data communications.

A result of this measurement or the maximum data size determined are exchanged between the plurality of communications devices connected to the network, and the maximum data size may also be determined in common between the plurality of communications devices.

According to another aspect of the present invention, a communications device comprises followings. The first is a network driving module for transmitting data to a network and

receiving the data from the network. The second is a control module for controlling communications by transferring and receiving the data to and from the network driving module. The third is a plurality of storage areas used for transferring and receiving the data between the network driving module and the control module. The fourth is a performance measuring module for measuring a data transferring/receiving time when transferring and receiving data having a different data size between the network driving module and the control module by use of the plurality of storage areas. The fifth is an optimum area obtaining module for obtaining an optimum storage area in which the data transferring/receiving time per data size using the specific storage area is under a data transferring/receiving time per data size using other storage area. The sixth is a selection module for selecting the optimum storage area in accordance with the data size when in communications.

According to still another aspect of the present invention, a readable-by-computer recording medium is recorded with a program for communications by switching over a plurality of communication modes. And the program comprises the following steps. The first is a step of measuring a communication performance in each of the communication modes under a plurality of communication conditions. The second is a step of obtaining, per communication condition, a condition-based optimum communication mode as a communication mode in which the communication performance in the specific communication mode exceeds a communication performance in other communication mode.

The third is a step of selecting the condition-based optimum communication mode in accordance with the communication condition when in communications, and thus performing the communications.

5           According to a further aspect of the present invention, a readable-by-computer recording medium is recorded with a program for communications by temporarily storing storage unit with transfer data restricted to a maximum data size as a basis for a data transfer. And the program comprises  
10 the following steps. The first is a step of operating the storage unit with a different operation quantity. The second is a step of measuring a completion time of each operation. The third is a step of obtaining a change in the completion time with respect to a change in the operation quantity. The forth is a step of  
15 determining the maximum data size within a range of the operation quantity in which the change in the completion time is within a predetermined value, and thus performing the communications.

As explained above, according to the present invention,  
20 the data communications are carried out based on the plurality of communication modes under the plurality of communication conditions between the communications devices connected to the network, and the communication performance in each communication mode under every communication condition, is  
25 evaluated. As a result, the optimum communication mode under each communication condition is obtained, and the optimum communication mode is selected based on the communication

condition when in communications. Accordingly, the communication performance between the communications devices connected to the network is automatically tuned.

Further, according to the present invention, the completion of the operation when operating the storage unit of the communications device with a plurality of operation quantities is measured. Then the maximum data size in the data communications is determined based on the measured completion time, whereby the communication performance is automatically tuned.

Moreover, according to the present invention, in the case of transferring and receiving the data between the network driving module and the control module, the data having a plurality of data sizes are transferred and received by use of a plurality of storage areas. As a consequence, an optimum storage area is determined, and the optimum storage area used for the transferring and receiving the data is selected based on the data size when in the data communications. Hence, the communication performance is automatically tuned.

The communication performance described above is periodically evaluated, and therefore the communication performance is periodically tuned.

The computer reads the program recorded on the recording medium and executes this program, thereby carrying out the communications method of the present invention and providing a function as the communications device of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an architecture of hardware of a communications device in a first embodiment;

5        FIG. 2 is a block diagram showing an architecture of a program executed in the communications device in the first embodiment;

FIG. 3 is a diagram showing one example of a communication mode;

10       FIG. 4 is a diagram showing one example of a communication mode;

FIG. 5 is a diagram showing one example of a result of measuring a communication performance;

15       FIG. 6 is a flowchart showing a procedure of selecting the communication mode in the first embodiment;

FIG. 7 is a diagram showing one example of a result of measuring the communication performance;

FIG. 8 is a diagram showing one example of the result of measuring the communication performance;

20       FIG. 9 is a flowchart showing a procedure of selecting the communication mode in a modified example of the first embodiment;

25       FIG. 10 is a flowchart showing a procedure of selecting the communication mode in a modified example of the first embodiment;

FIG. 11 is a block diagram showing an architecture of a program executed in the communications device in a second



embodiment;

FIG. 12 is a diagram showing one example of a result of measuring the communication performance;

FIG. 13 is a diagram showing one example of the result  
5 of measuring the communication performance;

FIG. 14 is a block diagram showing an architecture of a program executed in the communications device in a third embodiment;

FIG. 15 is a block diagram showing an architecture of a  
10 program executed in the communications device in the third embodiment;

FIG. 16 is a diagram showing one example of a result of measuring the communication performance; and

FIG. 17 is a flowchart showing a procedure of selecting  
15 a buffer mode in the third embodiment.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will hereinafter be described with reference to the accompanying  
20 drawings.

##### (First Embodiment)

Referring to FIGS. 1 through 6, a communications device in a first embodiment will be explained. FIG. 1 is a block diagram showing a hardware architecture of the communications  
25 device in the first embodiment. FIG. 2 is a block diagram showing a program architecture of the communications device. FIGS. 3 and 4 are diagrams each showing a communication mode

between a communications device 1 and another communications device 1a which are illustrated in FIG. 2. FIG. 5 is a chart showing an example of measured results (corresponding to a communications performance) of a communication time between the communications device 1 and the communication device 1a. FIG. 6 is a flowchart showing processes by a communications driver 4 shown in FIG. 2.

<Construction>

FIG. 1 is the block diagram showing the hardware architecture of the communications device 1 in the first embodiment. The communications device 1 includes, a CPU 11, a memory 12 (corresponding to a storage unit) for storing a program executed by the CPU 11 and data used in the CPU 11, and a communications board 13 controlled by the CPU 11 for performing communications with the communications device 1a on a network. The communications device 1 is connected via the communications board 13 to the network 2, and constitutes a node #0 on the network 2. The communications device 1 implements the data communications with the other communications device 1a constituting a node #1 on the network 2.

FIG. 2 is the block diagram showing the architecture of the program executed by the CPU 11 of the communications device 1 in the first embodiment. In the communications device 1, as shown in FIG. 2, the memory 12 has an OS 3 (corresponding to a control module) for controlling the data communications and a communications driver 4 (corresponding to a network driving module) operated by the OS 3.

The OS 3 receives the data from an unillustrated application program executed by the CPU 11 in the data communications with the communications device 1a connected to the network 2. The OS 3 transfers the data to the communications driver 4, and controls the data communications.

The communications driver 4 has a SEND mode module 5 for executing communications based on a SEND mode, a SEND-GET mode module 6 for executing communications based on a SEND-GET mode, an evaluation engine 7 (corresponding to a performance measuring module and a optimum mode obtaining module) for evaluating a communication performance of each of the SEND mode module 5 and the SEND-GET mode module 6, a node information table 8 for storing results of evaluation by the evaluation engine 7, and a selection module 9.

The communications driver 4 accepts a communication request from the OS 3. Based on this communication request, the communications driver 4 transmits the communication data to the network 2 or receives the communication data from the network 2. On this occasion, the communications driver 4 selects any one of the communication modes handled by the SEND mode module 5 and the SEND-GET mode module 6, and transmits and receives the communication data.

The SEND mode module 5 is a module of the communications driver 4, which performs the communications based on the SEND mode. The SEND mode is herein defined as a communication mode of directly transferring, as shown in FIG. 3, the data to the receiving-side communications device 1a from the

transmitting-side communications device 1.

On the other hand, the SEND-GET mode module 6 is a module of the communications driver 4, which performs the communications based on the SEND-GET mode. The SEND-GET mode is herein defined as a communication mode in which the receiving-side communications device 1a, as shown in FIG. 4, reads the data from the transmitting-side communications device 1. Therefore, to start with, the transmitting-side communications device 1 transmits only a header of the communication data to the receiving-side communications device 1a, and a data address is designated on the memory 12 in the communications device 1. Subsequently, the receiving-side communications device 1a reads the data from the designated address on the memory 12 of the transmitting-side communications device 1.

According to the SEND mode, the data transfer is completed by one transmitting/receiving process via the network 2. By contrast, the SEND-GET mode requires two transmitting/receiving processes via the network 2. While in the SEND mode, there might occur an extra process of copying the communication data via a transmitting/receiving buffer 25 in the communications drivers 4 or the OSs 3 in the transmitting-side communications device 1 and the receiving-side communications device 1a. By contrast, according to the SEND-GET mode, the communication data are read directly from the memory 12 of the transmitting-side communications device 1 and transferred to the receiving-side

communications device 1a. Hence, there occurs no extra process of copying via the communications oriented buffer. Generally speaking, it is therefore difficult to determine which communication mode is more advantageous.

5           The evaluation engine 7 evaluates communication performances in terms of evaluating a communication time (communication speed) when the SEND mode module 5 and the SEND-GET mode module 6 perform the communications.

10           FIG. 5 exemplifies evaluation results. FIG. 5 shows one example of the results of measuring the communication time in each of the SEND mode and the SEND-GET mode by varying a data size. Referring to FIG. 5, the communication time based on the SEND mode is shorter than the communication time in the SEND-GET mode till the communication data size is 1024 bytes. With  
15           respect to a data size exceeding 2048 bytes, however, the communication time based on the SEND-GET mode is shorter than the communication time in the SEND mode. Such being the case, the communications device 1 (and the communications device 1a) switches the SEND mode and the SEND-GET mode for use.

20           The data size, i.e., 2048 bytes in this example, serving as a criterion for such a judgement may be called a threshold value. The evaluation engine 7 writes to a node information table 8 both of this threshold value and a communication mode (the SEND mode in the measured result in FIG. 5) that should  
25           be used for a data size under the threshold value. A combination of the threshold value and the communication mode which should be used for the data size under the threshold value, corresponds

to a condition-based optimum communication mode.

The selection module 9 reads the threshold value measured by the evaluation engine 7 from the node information table 8 as described above, and judges whether or not a communication data size is equal to the threshold value or under. As a result, the selection module 9 selects one of the SEND mode and the SEND-GET mode, thus switching the communication mode.

<Example of Operation>

Next, an example of the operation of the communications device 1 shown in FIG. 2 will be explained. In advance of performing the communications, the evaluation engine 7 of the communications driver 4 judges whether or not the threshold value has already been set for the data communications with the communications device 1a serving as a co-communication node. Therefore, the evaluation engine 7 reads contents of the node information table 8. As a consequence, if the threshold value for the data communications with the communications device 1a is not yet set (viz., the communications device 1 performs the communications with the communications device 1a for the first time), the evaluation engine 7 measures beforehand a time of communications with the communications device 1a as shown in FIG. 5. Then the evaluation engine 7 writes a result of this measurement (a threshold value and data for indicating which communication mode is more advantageous if under the threshold value) to the node information table 8.

Next, the data communications are actually carried out in accordance with the flowchart shown in FIG. 6. To begin with,

the selection module of the communications driver 4 reads the threshold value and the communication mode (the SEND mode in the first embodiment) that should be used when under the threshold value from the node information table 8 (step 101 which will hereinafter be abbreviated to S101). Next, the selection module 9 of the communications driver 4 compares a communication data size with the threshold value (S102). If the communication data size is under the threshold value, the communications driver 4 performs the communications in the SEND mode (S103). Whereas if the communication data size is over the threshold value, the communications driver 4 performs the communications in the SEND-GET mode (S104).

Thus, the communications driver 4 automatically selects an optimum communication mode corresponding to the communication condition (which is the communication data size in this case), and hence the communication speed can be increased.

<Modified Example>

In accordance with the first embodiment, there is determined the threshold value for switching the communication mode from the SEND mode to SEND-GET mode and vice versa, and the communication mode is switched over based on whether or not the communication data size is under the threshold value. The threshold value is not limited to one single value. For example, if the result shown in FIG. 7 is obtained as a communication time, the SEND mode communications are more advantageous when the data size is less than 2048 bytes

(threshold value 1) than in the SEND-GET mode. Further, if the data size falls within a range of 2048 bytes through 16384 bytes (threshold value 2), the communications in the SEND-GET mode are more advantageous. Moreover, if the data size exceeds 16384  
5 bytes, the SEND mode communications again become more advantageous.

In such a case, as shown in the flowchart in FIG. 9, there are retained a plurality of threshold values for segmenting the data size into a plurality of data fields, and the communication  
10 mode may be determined by comparing the communication data size with the plurality of threshold values.

When the number of threshold values increases, in a process of making a plurality of judgements as shown in the flowchart in FIG. 9, the communication speed becomes rather  
15 lower due to a processing time for that judgement. This being the case, there is provided a table containing entries each consisting of, e.g., 256 bytes as a basic unit of data size as shown in FIG. 8. Then, in accordance with the following formula (1), the selection module 9 determines which entry the  
20 communication data size corresponds to, and may select the communication mode described in the entry indicated by that entry number.

$$\text{Table Entry Number} = \frac{\text{Communication Data Size}}{\text{Data Size Unit}} \quad (\text{Formula 1})$$

25 FIG. 10 is a flowchart showing processes based on those entry numbers in that table.

The first embodiment has exemplified the SEND mode



communications and the SEND-GET mode communications by way of the communication modes. The embodiments of the present invention are not, however, limited to those communication modes. In short, according to the present invention, at first, the data communications are previously implemented under the plurality of communication conditions between the plurality of communications devices capable of performing the data communications based on the plurality of communication modes, thereby measuring the communication time in each of the communication modes. Next, the communication mode in the actual communications is determined based on the measured result. Accordingly, the present invention is not confined to the communication mode itself.

Further, the communication mode is not restricted to the above two categories in order to carry out the present invention. Namely, if the communication modes for use are written beforehand to the entries in the table as shown in FIG. 8, a communication mode conceived optimal may be selected from three or more communication modes. Then the communications can be performed in this selected mode.

The communications device in the first embodiment uses the communication data size as the communication condition. However, instead of the data size, for instance, a communication time zone, a version of the OS 3 of the communications device 1a as a co-communication node, etc. may also be used as communication conditions. That is, the communication time (or communication speed) is previously measured for the above two

communication modes under those communication conditions, and an optimum communication mode is obtained per communication condition. Then, the optimum communication mode may be selected based on the communication condition when effecting the actual communications.

In the first embodiment discussed above, if the threshold value for the data communications with the communications device 1a serving as the co-communication node is not yet set in the node information table 8 (i.e., the communications device 1 performs the communications with the communications device 1a for the first time), the evaluation engine 7 measures the communication performance. Even if the threshold value has already been set, and if there is a time-elapse over a predetermined time from a point of time when the setting has been done, the threshold value may also be set by re-measuring the communication performance. For attaining this, when setting the threshold value, the evaluation engine 7 reads a date and a time thereof from a calendar incorporated into the OS 3 and records these pieces of data in a memory 12. As in the first embodiment discussed above, the communication time (or communication speed) is measured when starting the communications, and it is preferable that the threshold value be set. The communication time (or communication speed) may be, however, measured during the communications.

#### <Recording Medium Readably by Computer>

The communications driver 4 executed by the CPU 11 in the first embodiment may also be recorded on a recording medium

readable by a computer. The communications driver 4 is read and executed by the computer provided with the communication board 13 as shown in FIG. 1, whereby the functions of the communications devices 1, 1a shown in the first embodiment can  
5 be provided.

The readable-by-computer recording medium herein embraces recording mediums, readable by the computer, for storing pieces of information such as data and programs electrically, magnetically, optically, mechanically and  
10 chemically. Among those recording mediums, what can be removed from the computer may be, e.g., a floppy disk, a magneto-optic disk, a CD-ROM, a CD-R/W, a DVD, a DAT, an 8mm tape, a memory card, etc..

Further, the recording mediums fixed to the computer are  
15 a hard disk, ROM (Read-Only Memory), etc..

<Computer Data Signal Embodied in Carrier Wave>

Further, the communications driver 4 of the communications device 1 is stored in the hard disk or the memory of the computer, and can be distributed to other computers via  
20 the communication medium. In this case, the communications driver 4 is transmitted via the communication medium by way of computer data signals embodied in carrier waves. Then, the computer receiving the communications driver 4 can be thereby made to function as the communications device 1 in the first  
25 embodiment.

The communication medium herein includes wire communication mediums (an optical communication cable,

metallic cables including a coaxial cable and a twist paired cable, etc.), and wireless communication mediums (satellite communications, ground wave wireless communications, etc.).

Further, the carrier wave is categorized as an  
5 electromagnetic wave for modulating the computer data signal ,  
and includes the light and a DC signal. Accordingly, the  
computer data signal embodied in the carrier wave may have a  
broadband waveform modulated or a base band waveform  
unmodulated. That is, the computer data signal takes the base  
10 band waveform in the case of utilizing the DC signal having a  
voltage of 0 as a carrier wave.

(Second Embodiment)

A second embodiment of the present invention will be  
discussed with reference to FIGS. 11 through 13. FIG. 11 is  
15 a block diagram showing a program architecture in the  
communications device in the second embodiment. FIGS. 12 shows  
a result of measuring a time needed for allocating areas on the  
memory 12 (which is hereinafter termed a memory allocation) in  
the communications device 1 shown in FIG 11. FIGS. 13 shows a  
20 time needed for freeing the areas on the memory 12 (which is  
hereinafter referred to as memory free) (The memory allocation  
and the memory free correspond to operating a storage unit).

In the first embodiment discussed so far, the data  
communications are executed under the plurality of  
25 communication conditions between the plurality of  
communications devices capable of performing the data  
communications in the plurality of communication modes. And the

evaluation engine 7 measures the communication time based on each of the communication time. Then, based on the results thereof, the selection module 9 of the communications device determines the communication mode when in the actual

5 communications. While on the other hand, the second embodiment deals with the communications device capable of varying a maximum data size defined as a basis for transferring the data in the data communications with other communications devices connected to the network 2. The communications device  
10 determines the maximum data size as the basis for the data transfer in the data communications, from a time required for the memory allocation and a time needed for the memory free.

The maximum data size as the basis for the data transfer is herein defined as a maximum size of the data transferable  
15 when implementing one single data transfer prescribed by the communication protocol as in the case of the maximum packet size in, e.g., Ethernet.

FIG. 11 is the block diagram showing a program of the communications device 1 in the second embodiment. Referring  
20 to the block diagram in FIG. 11, the communications driver 4 includes a memory allocation module 15, a memory freeing module 16 (the memory allocation module 15 and the memory freeing module 16 in combination correspond to a storage unit operating module), and a determination module 19 for determining the  
25 maximum data size. Other configurations and operations are the same as those in the first embodiment, and hence the same components are marked with the like numerals, of which the

explanations are herein omitted. Further, the hardware architecture in the second embodiment is the same as that in the first embodiment, and will be explained referring to FIG. 1.

5 Referring to FIG. 11, the memory allocation module 15 is executed by the communications driver 4. As a result, a memory area with an allocation size designated on the memory 12 of the communications device 1, is allocated. While on the other hand, the memory freeing module 16 frees a designated memory area  
10 segment in the memory area allocated by the memory allocation module 15. The evaluation engine 7 executes the memory allocation module 15 and the memory freeing module 16, and evaluates an execution time thereof. The evaluation engine 7 corresponds to a performance measuring module and a calculation  
15 module.

The determination module 19 determines the maximum data size based on this execution time, and writes the maximum data size to the node information table 8. Thereafter, the maximum data size is used as a basis for the data transfer in the  
20 communications driver 4. For example, if a data transfer request for data exceeding the maximum data size is given to the communications driver 4, the data in the communications driver 4 is segmented into pieces of data each under the maximum data size, and thus transferred.

25 FIGS. 12 and 13 show one examples in which the evaluation engine 7 executes the memory allocation module 15 and the memory freeing module 16 and evaluates the execution time thereof. FIG.

12 shows the result of measuring the execution time when the evaluation engine 7 executes the memory allocation module 15 by changing the allocation size on the memory. As shown in FIG 12, when the allocation size is set to 16253 bytes, the execution time increases by one or more digits as compared with allocation sizes under 16253 bytes.

FIG. 13 shows the result of measuring the execution time by the evaluation engine 7 when the evaluation engine 7 executes the memory freeing module 16 to free the memory area segment allocated by the memory allocation module by varying the allocation size on the memory as described above. When the memory area segment with its allocation size set to 16253 bytes is freed, the execution time also increases by over one digit as compared with the allocation sizes under 16253 bytes, and an execution efficiency sharply declines.

In the communications device 1 in the second embodiment, the determination module 19 obtains an allocation size (16253 bytes in this case) with which the execution time when in such a memory allocation process or memory freeing process discontinuously changes to a deteriorated state, and retains this allocation size in the node information table 8. This may be determined by checking for every execution time whether or not a difference between the execution times changes by a fixed value or larger (or at over a fixed ratio).

This maximum data size is determined when the communications device 1 starts the communications with the communications device 1a serving as the co-communication node.

In the communications device 1, an operation oriented memory area (buffer area) for communications is allocated owing to the above maximum data size. Therefore, as a result of the setting described above, when performing the communications, the memory allocation and the memory freeing are done with such an allocation size that the execution efficiency does not decline. Accordingly, if the execution time relative to the memory allocation changes depending upon a change in version of the OS 3, a change in the clock cycle of the CPU 11 in the communications device 1, an extension of the memory 12, etc., it is feasible to prevent the concomitant decline of the execution efficiency of the communications driver 4.

<Modified Example>

In the embodiment discussed above, the maximum data size is determined based on the allocation size with which the allocation time or the freeing time changes to the deteriorated state. As a substitute for this method, the maximum data size may be determined based on such an allocation size that both of the allocation time and the freeing time change to the deteriorated state.

In accordance with the embodiment discussed above, the maximum data size is determined when the communications device 1, as explained above, starts the communications with the communications device 1a serving as the co-communications node. The maximum data size may also be, however, determined beforehand between the plurality of communications devices connected to the network 2. The maximum data size may be



determined so as to be common between the plurality of communications devices 1, 1a connected to the network 2. It may be done by exchanging the above-measured execution times for the memory allocation and for the memory freeing in each of the communications devices or the determined maximum data size in each of the communications devices. This common maximum data size may be determined by predetermined methods as a maximum value, a minimum value or an average value of the maximum data size determined in each of the communications devices.

The embodiment discussed above has exemplified the case where the maximum data size as the basis for the data transfer in the communications is determined based on the execution times for the memory allocation and the memory freeing in the communications driver 4. However, the present invention is not limited to this embodiment. Namely, the maximum data size may also be determined based on an execution time for other operations (writing, reading, etc.) with respect to the memory 12.

Further, the embodiment discussed above has exemplified the case where the maximum data size as the basis for the data transfer in the communications is determined based on the execution times for the memory allocation and the memory freeing. Instead of this method, the maximum data size may be determined by a conversion into an execution speed conceived as a memory operation quantity (capacity of the memory allocation, etc.) per unit time, and by detecting a region of the memory operation quantity with which the execution speed discontinuously

changes.

In the embodiment discussed above, when the communications device 1 starts the communications with the communications device 1a as the co-communications node, the evaluation engine 7 determines the maximum data size by measuring the execution times for the memory allocation and for the memory freeing. As a substitute for this method, the evaluation engine 7 periodically measures these execution times, and may thus determine the maximum data size. The determination thereof may involve such a process that the timer incorporated into the OS 3 periodically actuates the evaluation engine 7, and further the evaluation engine 7 starts up the determination module 19.

<Recording Medium Readable by Computer>

The communications driver 4 of the communications device 1 in the second embodiment can be recorded on a readable-by-computer recording medium. The communications driver 4 is read and executed by the computer including the communication board 13 as shown in FIG. 1, thereby providing a function of each of the communications devices 1, 1a shown in the second embodiment.

<Computer Data Signal Embodied in Carrier Wave>

The communications driver 4 of the communications device 1 is stored in the hard disk or the memory of the computer, and can be distributed to other computers via the communication medium. In this case, the program is transmitted via the communication medium by way of computer data signals embodied

in carrier waves. Then, the computer receiving the distribution thereof can be thereby made to function as the communications device 1 in the second embodiment.

The computer data signal embodied in the carrier wave may  
5 have a broadband waveform modulated or a base band waveform unmodulated (which implies a case of being modulated at a direct current having a voltage of 0).

(Third Embodiment)

A third embodiment of the present invention will be  
10 described with reference to FIGS. 14 through 17. FIGS. 14 and 15 are block diagram each showing a program architecture in the communications device in the third embodiment. FIG. 16 shows one example of a result of measuring a data  
15 transferring/receiving time between the OS 3 and the communications driver 4 in the communications device 1 illustrated in FIGS. 14 and 15. FIG. 17 is a flowchart showing processes of the OS 3 and of the communications driver 4 illustrated in FGS. 14 and 15.

In the third embodiment, the communications device 1 for  
20 tuning an access to an operation area (buffer area) used when in communications, will be explained.

The communications device 1 shown in FIG. 14 has the memory including a demon defined as an application program for communications with another communications device 1a. Further,  
25 the communications device 1 includes a communication buffer 21 serving as an operation area for storing the communication data transmitted and received by the demon 20, and a

transmitting/receiving data area 22 serving as an operation area of the communications driver 4. Other configurations and operations are the same as those in the first embodiment, and hence the same components are marked with the like numerals, of which the explanations are herein omitted.

The communication buffer 21 shown in FIG. 14 is provided in a memory area (segmental area on the memory 12) managed by the OS 3. Accordingly, the communications driver 4 copies the data used for the transmission and receipt to the memory area managed by the OS 3, thereby transferring and receiving the data to and from the OS 3. This process is hereinafter be called an OS buffer mode.

On the other hand, a communication buffer 23 shown in FIG. 15 is provided in a memory area (segmental area on the memory 12) managed by the communications driver 4. When transferring and receiving the data between the communications driver 4 and the OS 3, a head address in the communication buffer 23 is transferred to the OS 3, and the data is inputted and outputted by use of the area thereof. This process is hereinafter called a driver buffer mode.

It is recognized that a time required for transferring and receiving the data between the communications driver 4 and the OS 3 (and more essentially a communication time or communication speed) is influenced by buffer structure. The buffers based on the OS buffer mode and the driver buffer mode correspond to a plurality of storage areas.

The demon 20, in a variety of architectures based on the

OS buffer mode shown in FIG. 14 and the driver buffer mode shown in FIG. 15, implements the communications with the other communications device 1a via the OS 3 and the communications driver 4 while changing the data size. And the demon 20 measures the communication time (or communication speed) thereof. In the third embodiment, the demon 20 corresponds to a performance measuring module and an optimum area obtaining module. FIG. 16 shows one example of a result of the measurement.

Referring to FIG. 16, if the data size is less than 2048 bytes, the communication time in the OS buffer mode is shorter than in the driver buffer mode. Whereas if exceeding 2048 bytes, the communication time in the driver buffer mode is shorter than in the OS buffer mode. Such being the case, the data size on the order of 2048 bytes may be called a threshold value as in the first embodiment.

The demon 20 obtains the threshold value described above from the result of measuring the communication time as shown in FIG. 16. Then the demon 20 sets in the node information table 8 this threshold value and the buffer mode (the OS buffer mode in the example in FIG. 16) used in the communications for the data size under the above threshold value. A combination of the above threshold value and the buffer mode used in the communications for the data size under the threshold value, corresponds to an optimum storage area.

On the other hand, when performing the communications, the OS 3 and the communications driver 4 determine referring to the node information table 8 whether the OS buffer or the

driver buffer should be used corresponding to the communication data size. Then the OS 3 and the communications driver 4 transfer and receive the data to and from each other. FIG. 17 is a flowchart showing a processing procedure of determining the  
5 buffer mode in the OS 3 and the communications driver 4. A program (which implies the OS 3 and the communications driver 4 in the third embodiment) for executing the processes in the flowchart shown in FIG. 17 corresponds to the selection module.

The buffer mode exhibiting the shortest communication  
10 time (highest communication speed) is thus selected in accordance with the communication condition, and the data communications are carried out between the communications device 1 and the other communications device 1a.

<Modified Example>

15 As discussed above, the threshold value of the communication data size in the third embodiment is set in the node information table 8, and, based on this threshold value, the OS 3 and the communications driver 4 determine the buffer mode. Instead of this method, the OS 3 (or the communications  
20 driver 4) may determine the buffer mode, and the communications driver 4 (or the OS 3) may be notified of a result of this determination.

Note that a plurality of threshold values may also be provided as discussed in the first embodiment. Further, an  
25 entry number in the Table may be determined from the communication data size according to the formula 1 in the first embodiment, and the buffer mode for use may be designated in

each entry in the Table.

What has been discussed so far in the third embodiment is the communications device for effecting the communications by selecting an optimum buffer mode from the OS buffer mode and the driver buffer mode on the basis of the data size when in the communications. The embodiment of the present invention is not, however, confined to those buffer modes themselves. According to the present invention, the data of plurality of different data sizes are transferred and received via the respective buffers in the communications device, capable of using the plurality of buffer modes (or buffer areas). Then the transferring/receiving time thereof is measure beforehand. Then the optimum buffer mode per data size is obtained. Finally, the optimum buffer mode (or buffer area) is selected based on the data size when implementing the communications. Hence, the present invention does not depend upon the buffer mode itself.

The third embodiment has exemplified the method of selecting the optimum buffer mode from the two buffer modes, however, the present invention is not limited to this method. For instance, the present invention can be carried out in the communications between devices capable of using three or more buffer modes. It is done by adopting the method of writing the optimum buffer mode to the entry of a table which is indicated by the entry number calculated from the formula 1 shown in the first embodiment.

<Recording Medium Readable by Computer>

The programs such as the communications driver 4 and the

OS 3 or the demon 20 in the communications device 1 in the third embodiment can be recorded on the readable-by-computer recording medium. The program recorded on the recording medium is read and executed by the computer including the communication board 13 as shown in FIG. 1, whereby the function of each of the communications devices 1, 1a shown in the third embodiment can be provided. Incidentally, there is no necessity for recording all the programs such as the communications driver 4 and the OS 3 or the demon 20 on the same medium.

<Computer Data Signal Embodied in Carrier Wave>

The programs such as the communications driver 4 and the OS 3 or the demon 20 in the communications device 1 are stored in the hard disk or the memory of the computer, and can be distributed via the communication medium to other computers. In this case, the program is transmitted via the communication medium by way of computer data signals embodied in carrier waves. Then, the computer receiving the distribution thereof can be thereby made to function as the communications device 1 in the third embodiment.

Herein, the computer data signal embodied in the carrier wave may have the broadband waveform modulated and the base band waveform unmodulated (which implies a case of being modulated at a direct current having a voltage of 0). Note that there is no necessity for distributing all the programs such as the communications driver 4 and the OS 3 or the demon 20 via the communication medium. For example, the communications driver



4 or the OS 3 is recorded on the recording medium, and the demon  
20 may be distributed via the communication medium.

WHAT IS CLAIMED IS:

1. A communications method of performing communications by switching over a plurality of communication modes, comprising:

5       measuring a communication performance based on each of the communication modes under a plurality of communication conditions;

obtaining a condition-based optimum communication mode in which the communication performance in the specific  
10       communication mode exceeds a communication performance in other communication mode per communication condition; and

selecting the condition-based optimum communication mode in accordance with the communication condition when in communications, and thus performing the communications.

15       2. A communications device for performing communications by switching over a plurality of communication modes, comprising:

a performance measuring module for measuring a  
20       communication performance based on each of the communication modes under a plurality of communication conditions;

a optimum mode obtaining module for obtaining a condition-based optimum communication mode in which the communication performance in the specific communication mode  
25       exceeds a communication performance in other communication mode per communication condition based on the measured communication performance; and

a selection module for selecting the condition-based optimum communication mode in accordance with the communication condition when in communications. /

5           3. A communications method of temporarily storing storage unit with transfer data restricted to a maximum data size as a basis for a data transfer, comprising:

operating said storage unit with a different operation quantity;

10           measuring a completion time of each operation;

obtaining a change in the completion time with respect to a change in the operation quantity; and

determining the maximum data size within a range of the operation quantity in which the change in the completion time is within a predetermined value, and thus performing the communications.

4. A communications device capable of changing a maximum data size as a basis for a data transfer, comprising:

20           a storage unit for temporarily storing transfer data restricted to the maximum data size;

a storage unit operating module for operating said storage unit with a designated operation quantity;

a performance measuring module for measuring a completion time of each operation with said operation module operating said storage unit by designating a different operation quantity;

a calculation module for obtaining a change in the

completion time with respect to a change in the operation quantity; and

a determining module for determining the maximum data size within a range of the operation quantity in which the change  
5 in the completion time is within a predetermined value.

5. A communications device comprising:

a network driving module for transmitting data to a network and receiving the data from the network;

10 a control module for controlling communications by transferring and receiving the data to and from said network driving module;

a plurality of storage areas used for transferring and receiving the data between said network driving module and said  
15 control module;

a performance measuring module for measuring a data transferring/receiving time when transferring and receiving data having a different data size between said network driving module and said control module by use of said plurality of  
20 storage areas;

an optimum area obtaining module for obtaining an optimum storage area in which the data transferring/receiving time per data size using the specific storage area is under a data transferring/receiving time per data size using other storage  
25 area; and

a selection module for selecting the optimum storage area in accordance with the data size when in communications.

6. A readable-by -computer recording medium recorded with a program for communications by switching over a plurality of communication modes, said program comprising:

5       a step of measuring a communication performance in each of the communication modes under a plurality of communication conditions;

          a step of obtaining a condition-based optimum communication mode in which the communication performance in  
10 the specific communication mode exceeds a communication performance in other communication mode per communication condition; and

          a step of selecting the condition-based optimum communication mode in accordance with the communication  
15 condition when in communications, and thus performing the communications.

7. A readable-by -computer recording medium recorded with a program for communications by temporarily storing storage  
20 unit with transfer data restricted to a maximum data size as a basis for a data transfer, said program comprising:

          a step of operating said storage unit with a different operation quantity;

          a step of measuring a completion time of each operation;  
25       a step of obtaining a change in the completion time with respect to a change in the operation quantity; and

          a step of determining the maximum data size within a range

of the operation quantity in which the change in the completion time is within a predetermined value, and thus performing the communications.

5           8. A communications device according to claim 2, further comprising:

          means for storing the condition-based optimum communication mode,

          wherein said performance measuring module measures the  
10 communication performance in the communications with said other communications device if not stored with the condition-based optimum communication mode in the communications with other communications device when performing the communications with said other communications device, and

15           said optimum mode obtaining module obtains the condition-based optimum communication mode.

          9. A communications device according to claim 4, wherein  
20 pieces of information on the operation quantity and the completion time or the maximum data size are exchanged in said plurality of communications devices connected to each other, and

          said determining module determines the maximum data size  
in common to said plurality of communications devices connected  
25 to each other.

          10. A communications device according to claim 4, wherein

said performance measuring module periodically measures the completion time of the operation, and

said determination module periodically determines the maximum data size as a basis for the data transfer on the basis  
5 of the measured completion time.

11. A communications device according to claim 5, wherein said performance measuring module periodically measures the data transferring/receiving time.

ABSTRACT OF THE DISCLOSURE

Disclosed are a function of automatically tuning a communication performance between the communications devices connected to a network and a function of periodically confirming and tuning the communication performance. In a plurality of communications devices capable of performing the communications by switching over a plurality of communication modes, the communication performance in each of the communication modes is previously measured under a plurality of communication conditions, there is obtained, per communication condition, a condition-based optimum communication mode as a communication mode in which the communication performance in the specific communication mode exceeds a communication performance in other communication mode, the condition-based optimum communication mode is selected in accordance with the communication condition when in communications, and the communications are thus performed.



FIG. 1






FIG. 2



# FIG. 3



# FIG. 4




FIG. 5

DATA SIZE (Byte)	256	512	1024	2048	4096	8192	...
	21	23	26	28	29	31	...
COMMUNICATION TIME (m S)	SEND MODE	25	26	27	28	29	...
	SEND-GET MODE	25	26	27	28	29	...

FIG. 6




FIG. 7

DATA SIZE (Byte)		256	512	1024	2048	4096	8192	16384
COMMUNICATION TIME (ms)	SEND MODE	21	23	26	31	29	31	31
	SEND-GET MODE	25	25	26	27	28	29	34
THRESHOLD VALUE		2048 (THRESHOLD VALUE "1")		16384 (THRESHOLD VALUE "2")		--		
COMMUNICATION MODE		SEND MODE		SEND-GET MODE		SEND MODE		

FIG. 8

DATA SIZE (Byte)		256	512	1024	2048	4096	8192	16384
COMMUNICATION TIME (mS)	SEND MODE	21	23	26	31	29	31	31
	SEND-GET MODE	25	25	26	27	28	29	34
TABLE ENTRY NUMBER		0	...	...	8	...	...	64
COMMUNICATION MODE		SEND MODE		SEND-GET MODE		SEND MODE		

FIG. 9







FIG. 10



# FIG. 11





FIG. 12

DATA SIZE (Byte)	16000	16252	16253	32000	32768	65000	...
MEMORY ALLOCATION EXECUTION TIME (mS)	2	3	40	63	57	86	...

FIG. 13

DATA SIZE (Byte)	16000	16252	16253	32000	32768	65000	...
MEMORY FREE EXECUTION TIME (mS)	2	2	63	69	81	104	...

# FIG. 14



# FIG. 15





FIG. 16

DATA SIZE (Byte)	DATA SIZE					
	256	512	1024	2048	4096	8192
DATA TRANSMITTING/ RECEIVING TIME (ms)	21	23	26	28	29	31
OS BUFFER MODE	25	25	26	27	28	29
DRIVER BUFFER MODE						

FIG. 17



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Declaration and Power of Attorney For Patent Application

### 特許出願宣言書及び委任状

### Japanese Language Declaration

### 日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

COMMUNICATIONS METHOD AND

COMMUNICATIONS DEVICE

上記発明の明細書（下記の欄でx印がついていない場合は、本表に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を \_\_\_\_\_ とし、  
（該当する場合） \_\_\_\_\_ に訂正されました。

☐ was filed on \_\_\_\_\_  
as United States Application Number or  
PCT International Application Number  
\_\_\_\_\_ and was amended on  
\_\_\_\_\_ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Page 1 of

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner of Patents and Trademarks, Washington, DC 20231.



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration  
(日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一ヶ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

## Prior Foreign Application(s)

外国での先行出願  
11-231694

Japan

(Number)  
(番号)

(Country)  
(国名)

(Number)  
(番号)

(Country)  
(国名)

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

☐☐

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じているところに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行なえば、出願した、又は発明に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

# Japanese Language Declaration

## (日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の  
手続を米特許商標局に対して遂行する弁理士または代理人  
として、下記の者を指名いたします。(弁護士、または代理  
人氏名及び登録番号を用記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint  
the following attorney(s) and/or agent(s) to prosecute this  
application and transact all business in the Patent and Trademark  
Office connected therewith (list name and registration number)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358;  
William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul  
I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938;  
Michael C. Soldner, P-41,455 and William M. Schertler, 35,348 (agent)

書類送付先

Send Correspondence to:

STAAS & HALSEY  
700 Eleventh Street, N.W.  
Suite 500  
Washington, D.C. 20001

直接電話連絡先 (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY  
(202) 434-1500

唯一または第一発明者名	Full name of sole or first inventor	
	Kazuichi OOE	
発明者の署名	日付	Inventor's signature Date
		Kazuichi Ooe January 14, 2000
住所	Residence	
	Kawasaki-shi, Kanagawa, Japan	
国籍	Citizenship	
	Japanese	
私書箱	Post Office Address	
	c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa, 211-8588 Japan	
第二共同発明者	Full name of second joint inventor, if any	
第二共同発明者	日付	Second inventor's signature Date
住所	Residence	
国籍	Citizenship	
私書箱	Post Office Address	

(第三以降の共同発明者についても同様に記載し、署名を  
すること)

(Supply similar information and signature for third and subsequent  
joint inventors.)